

COMING



Sample photograph

DURMA model SBT4006

Swing Beam Touch Shear

Capacity

- 4100mm x 6mm mild steel (450 N/mm²)
- 4100mm x 4mm stainless steel (700 N/mm²)

Specification

- Standard

- Throat Depth 50mm
- 1000mm back gauge on ballscrews
- Automatic back gauge lift for cutting bigger than 1000mm
- Single point blade gap adjustment
- 0.05mm to 0.75mm blade gap adjustment
- 20 hold down jacks
- 1°30' blade rake angle
- shadow line
- ball transfer table
- 1 x 1500mm squaring arm
- 3 x 1000mm sheet support arms with flip stops
- movable foot pedal

- Optional

- Motorized blade gap adjustment link to controller
- Laser Cutting Line
- Pneumatic sheet support device
- 350 or 500mm Throat

Leabourn & Rose Ltd

Address: 87 Springs Road, East Tamaki, Auckland

Email: sales@leabourn-rose.co.nz

Web: www.leabourn-rose.co.nz

Phone: (09) 274 6186 Fax: (09) 274 0976

DURMA model SBT 4006

CNC Touch Screen Control Unit



- Large Colour Touch Screen, LCD: 7", 800 x 480 Display
- Rapid data input
- Easy communication, USB Port for USB flash memory
- Ethernet RJ-45 10/100M
- Operation System: Windows CE
- User Program and Steps: Unlimited
- Material Type: Unlimited

P.O.A

Ex our stock

* All prices quoted apply only to our stock machine(s), subject to prior sale. All prices are plus GST ex our store East Tamaki, Auckland. For full sales terms refer to: http://www.leabourn-rose.co.nz/terms_cond.htm
A copy of our terms & conditions is available on request. Leabourn & Rose has made every attempt to ensure the content of this flyer is correct, however all manufacturers reserve the right to change specifications and prices without notification.