



# HARDINGE®

EXPECT MORE™

## Performance CNC Lathes



**GS 150**  
**GS 200**

Machining 284mm dia x 406mm  
 Spindle 6,000 rpm (GS 150)  
 5,000 rpm (GS 200)  
 Bore 150mm chuck 45mm bore  
 200mm chuck 52mm bore  
 Controller Fanuc OiTC or Siemens 828D (Shopturn)  
 Options Live tooling  
 Swarf management  
 Tool probe



**GS 200 / 66**  
**GS 250**

Machining 356mm dia x 600mm  
 Spindle 4,200 rpm (GS 200 / 66)  
 3,500 rpm (GS 250)  
 Bore 200mm chuck 66mm bore  
 250mm chuck mm bore  
 Controller Fanuc OiTC or Siemens 828D (Shopturn)  
 Options Live tooling  
 Swarf management  
 Tool probe



**GS 200 / 66 L**  
**GS 250 L**

Machining 356mm dia x 1050mm  
 Spindle 4,200 rpm (GS 200 / 66)  
 3,500 rpm (GS 250)  
 Bore 200mm chuck 66mm bore  
 250mm chuck 78mm bore  
 Controller Fanuc OiTC or Siemens 828D (Shopturn)  
 Options Live tooling  
 Swarf management  
 Tool probe

**Leabourn & Rose Ltd – Ph (09) 274 6186 – sales@leabourn-rose.co.nz**